



TEMPERATURE CONTROL FOR TODAY & TOMORROW



FDC1000KXZRE2
100.0 KW



Specificații tehnice

Combinatii posibile (FDC)				500KXZRE2 + 500KXZRE2
Capacitate nominala (cai putere)				36HP
Sursă de alimentare				Trifazic 380-415V, 50Hz
Putere de pornire			A	16
Curent maxim admis			A	82.0
Capacitate nominala	Racire		kW	100.0
	Incalzire			100.0
Consumul de energie		Racire	kW	30.40
		Incalzire		25.38
Dimensiuni exterioare	I/L/A		mm	2052x2700x720
Greutate netă			kg	840
Refrigerant	Tip / GWP			R410A
Incarcare refrigerant	R410A		kg	11.5x2
Dimensiuni țeavă refrigerant	Refrigerant lichid		mm(in)	ø15.88(5/8")
Dimensiuni țeavă refrigerant	Admisie refrigerant gazos		mm(in)	ø38.1(1 1/2")[ø34.92(1 3/8")]
Dimensiuni țeavă refrigerant	Refulare refrigerant gazos		mm(in)	ø28.58(1 1/8")
Capacitatea minima/maxima acceptata			%	50~130
Numarul maxim de unitati interne acceptate				80



All measurements in mm.

