



TEMPERATURE CONTROL FOR TODAY & TOMORROW



FDC1060KXZRE2
106.0 KW



Specificații tehnice

Combinatii posibile (FDC)				500KXZRE2 + 560KXZRE2
Capacitate nominala (cai putere)				38HP
Sursă de alimentare				Trifazic 380-415V, 50Hz
Putere de pornire			A	16
Curent maxim admis			A	82.6
Capacitate nominala	Racire		kW	106.0
	Incalzire			106.0
Consumul de energie		Racire	kW	34.51
		Incalzire		27.62
Dimensiuni exterioare	I/L/A		mm	2052x2700x720
Greutate netă			kg	840
Refrigerant	Tip / GWP			R410A
Incarcare refrigerant	R410A		kg	11.5x2
Dimensiuni țeavă refrigerant	Refrigerant lichid		mm(in)	ø19.05(3/4")
Dimensiuni țeavă refrigerant	Admisie refrigerant gazos		mm(in)	ø38.1(1 1/2")[ø34.92(1 3/8")]
Dimensiuni țeavă refrigerant	Refulare refrigerant gazos		mm(in)	ø31.75(1 1/4")[ø28.58(1 1/8")]
Capacitatea minima/maxima acceptata			%	50~130
Numarul maxim de unitati interne acceptate				80



All measurements in mm.

