



TEMPERATURE CONTROL FOR TODAY & TOMORROW



FDC800KXZRE2
80.0 KW



Specificații tehnice

Combinatii posibile (FDC)				400KXZRE2 + 400KXZRE2
Capacitate nominala (cai putere)				28HP
Sursă de alimentare				Trifazic 380-415V, 50Hz
Putere de pornire			A	10
Curent maxim admis			A	60.0
Capacitate nominala	Racire		kW	80.0
	Incalzire			80.0
Consumul de energie		Racire	kW	23.12
		Incalzire		19.52
Dimensiuni exterioare	I/L/A		mm	2052x2700x720
Greutate netă			kg	744
Refrigerant	Tip / GWP			R410A
Incarcare refrigerant	R410A		kg	11.5x2
Dimensiuni țeavă refrigerant	Refrigerant lichid		mm(in)	ø15.88(5/8")
Dimensiuni țeavă refrigerant	Admisie refrigerant gazos		mm(in)	ø31.75(1 1/4") [ø34.92(1 3/8")]
Dimensiuni țeavă refrigerant	Refulare refrigerant gazos		mm(in)	ø28.58(1 1/8")
Capacitatea minima/maxima acceptata			%	50~160
Numarul maxim de unitati interne acceptate				80



All measurements in mm.

