




TEMPERATURE CONTROL FOR TODAY & TOMORROW




FDUM45KXE6F

4.5 KW



Specificații tehnice

Capacitate nominală de răcire		kW	4.5
Capacitate nominala de incalzire		kW	5.0
Sursă de alimentare			Monofazic 220-240V, 50Hz
Consumul de energie	Racire	kW	0.10-0.10
	Incalzire	kW	0.10-0.10
Nivel putere sonoră		dB(A)	60
Nivel de presiune sonoră racire		db(A)	P-Hi: 37 Hi:32 Me:29 Lo:26
Dimensiuni exterioare unitate	I x L x A	mm	280 x 750 x 635
Greutate netă		kg	29
Flux de aer		m ³ /min	P-Hi: 13 Hi:10 Me:9 Lo:8
Presiunea statica externa maxima		Pa	100
Aport de aer proaspat			Este posibil
Filtru de aer			Kit filtru::UM-FL1EF/UM-FL2EF/UM-FL3EF (opționalal)
Telecomanda (opționalal)			Cu fir: RC-EX3A, RC-E5, RCH-E3 Fara fir: RCN-KIT4-E2
Dimensiuni țeavă refrigerant		mm(in)	Refrigerant lichid: ø6.35(1/4") Refrigerant gazos: ø12.7(1/2")

[illegible]

Symbol	Model	Content
		22.28 36.45.56
A	Gas piping	#9.52 (3/8") (Flare) #12.7 (1/2") (Flare)
B	Liquid piping	#6.35 (1/4") (Flare)
C1	Drain piping	VP25 (0.0,3.32)
C2	Drain piping (Gravity drainage)	VP20
D	Hot for wiring	
E	Suspension balls	(M10)
F	Outside air opening for ducting	(Knock out)
G	Air outlet opening for ducting	(Knock out)
H	Refrigerant piping	#6.35 (1/4")

Note: The model name label is attached on the lid of the control box.

